

MINİ RÖLELER MICRO RELAYS



ELO Kodu Code: 201.003.001 (30 A 12V / 5 Terminals) / 201.003.002 (30 A 12V / 4 Terminals)

201.003.003 (20 A 24V / 5 Terminals) / 201.003.004 (20 A 24V / 4 Terminals)



ELO Mini Röle 12V / 30A 4 fişli, 12V / 30A 5 fişli, 24V / 20A 4 fişli, ve 24V / 20A 5 fişli olmak üzere dört farklı tipte üretilmektedir.

ELO Mini Röle'nin her dört tipinde de bobin sarımları sürekli enerji altında kalmaya uygun olarak tasarlanmıştır. **ELO Mini Röle**'ler neme, vibrasyona ve tüm dış etkilere son derece dayanıklıdır.

ELO Micro Relay is produced in four different types, being 12V / 30A with 4 plugs, 12V/30A with 5 plugs, 24V / 20A with 4 plugs and 24V / 20A with 5 plugs.

The coil wiring of all four types of the **ELO Micro Relay** are designed resistant to a continuous flow of current.

ELO Micro Relay is extremely resistant to moisture, vibration and other external influences.

Ambalaj / Packing


24 Adetlik Kutularda / 24 pcs. in a box 400 Adetlik Koli / 400 pcs. in a coli

Kargo Koli Boyutları (En x Boy x Yükseklik)
Export Coli Dimensions (W x H x E)


36.5 cm x 32 cm x 20.5 cm

Teknik Özellikler / Technical Specifications


	30A (4-5 terminals)	20A (4-5 terminals)
Çalışma Gerilimi / Operation Voltage	8-16V DC	20-30V DC
Kontak Akımı / Contact Current	30A	20A
Lamba Yüğü Gücü / Bulb Load Power	420W	420W
Ortam Harareti / Ambient Temperature	-40 °C / +90 °C	-40 °C / +90 °C
Bobin Direnci / Coil Resistance	70Ω	300Ω
Ağırlık (Şase Demirli) / Weight	32 gr.	32 gr.



4 Fişli / 4 Terminals



5 Fişli / 5 Terminals



BAĞLAR MAHALLESİ FATİH CADDESİ BARIŞ SOKAK 18 GÜNEŞLİ 34550 İSTANBUL

TEL : +90.212.630 51 78 +90.212.630 51 81 +90.212.630 51 91 +90.212.630 51 92 +90.212.630 51 97

FAX : +90.212.630 51 24

e-mail : info@elo.com.tr http://www.elo.com.tr